



# COMPACT DOME



Fixed lens compact dome with IR



Versatile, lightweight, and fit for discreet indoor installations



High resolution (5MP) and extreme low light performance (f/1.3)



Built-in AI video and audio analytics and on-device storage



Factory-installed certificates backed by a trusted platform module (TPM)



NDAA-compliant: designed and developed in Norway and the UK, manufactured in Taiwan



#### Image sensor

5MP (4:3)

#### Image sensor size format

1/2.7"

#### Lens

Focal length: 3.2mm

Aperture: f/1.3 Fixed focus

#### IR night vision

Automatic night mode

IR-cut filter IR range: 10m 850 nm IR LED

#### Minimum illumination in color mode

0.10lux

#### Field of view

102° Horizontal 71° Vertical

#### Maximum resolution & Frame rate

2688x1944@30fps

#### Dynamic range

Multi-exposure line-based HDR

#### Video compression

H.265, H.264, Motion JPEG

#### **Audio**

Microphone

Audio classification

#### Security

Trusted Platform Module (TPM 2.0)
Factory-installed certificates
No default passwords
Mandatory access authentication
HTTPS/TLS encryption

#### **Network protocols**

IPv4, HTTPS, TLS, DNS, mDNS, DNS-SD, NTP,

RTSP, RTP, RTCP, ICMP, DHCP, ARP

Streaming: RTP/UDP, RTP/RTSP/HTTPS/TCP

#### Power source

PoE 802.3af

USB-C, installation only

#### Power consumption

Typical: 5W Max: 8W

#### Storage

2x MicroSD, SDXC UHS-I

#### Connection

802.3ab 10/100 Ethernet USB-C for preview and setup

#### Installation aid

Mount template

Screws and wall plugs included

1/4-20 UNC standardized camera mount

thread

#### Adjustment range

Pan, Tilt, Roll

#### **Temperature**

Operating: 0°C to +40°C Storage: -40°C to +60°C

#### Physical characteristics

Dimensions: 107x107x64mm

Weight: 280g

#### **EMC**

EN 55032, EN 61000-3-2/-3, EN 55024, EN 55035, EN 61000-6-1/-3, EN61000-6-2/-4, FCC Part 15B, ICES-003 Issue 6


#### Safety

IEC62368-1, UL62368-1, IEC62471




## Technical drawings

### Side view



### **Bottom view**





## Ordering information

## **Ava Compact Dome**

PRODUCT ID	ONBOARD RETENTION	DEPLOYMENT	COLOR
COMPACTDOME-W-5MP-30	30 days	Aware Cloud	White
COMPACTDOME-B-5MP-30	30 days	Aware Cloud	Black
COMPACTDOME-W-5MP-60	60 days	Aware Cloud	White
COMPACTDOME-B-5MP-60	60 days	Aware Cloud	Black
COMPACTDOME-W-5MP-120	120 days	Aware Cloud	White
COMPACTDOME-B-5MP-120	120 days	Aware Cloud	Black
COMPACTDOME-W	No	Aware on-prem	White
COMPACTDOME-B	No	Aware on-prem	Black

## Accessories

PRODUCT ID	RESOLUTION	COLOR
ACC-DRO-CEI	Drop Ceiling mount	N/A